PAYPOINT WINDOWS



Chubbsafes

Trusted the world over.

PAYPOINT WINDOWS

PW1

Gunnebo Paypoint Windows are installed within office walls, doors or partitioning to protect against physical or ballistic attack. Four models offer a choice of protection levels for both internal and external environments.

DESIGN FRAME AND TRAY

All the windows feature a stainless-steel frame and transaction tray. The tray is available in a range of sizes and the frame allows natural voice transference in both directions.

BASE

All internal windows are fitted with a rectangular base which is inlaid with linoleum (blue/grey as standard) and finished at the edges in ash veneer. For deeper transaction trays (PW1), an additional box is fitted beneath the base, with a Wedgwood blue laminate finish.

EXTERNAL WINDOWS

The external windows (PW4) features a spring-hinged transaction tray which folds and locks against the frame. When the tray is open it provides a 25mm deep tray and natural voice transference. When closed, draughts are fully excluded.

AVAILABLE MODELS

The suitability of the window for internal and external environments, wall, partition or door installation, larger or smaller documents is detailed in table 1 below



Chubbsafes

Trusted the world over.

APPLICATIONS

Paypoint windows are suitable for protecting cash and staff in all areas where there is a possible risk of robbery or violent assault. Ticket offices, payment booths and cash offices are usual environments in which the windows are used.

When specifying installations, note that all surrounding walls, doors and partitioning should provide levels of protection against attack which are equivalent or higher than levels offered by the windows.

SERVICE AND MAINTENANCE

A range of maintenance and customer support contracts are available if required.

PW4 PW3











TABLE 1: **AVAILABLE MODELS**

Position of Window		Document Size	Model	Tray Depth mm	Structural Width mm	Opening Height mm	Glass Thickness mm	Weight kg
Internal	Wall	Large	PW1	57 113	523	930	13.5 36.5 42	38 55 60
		Standard	PW2	19	523	800	13.5 36.5 42	25 42 47
	Partition or door	Standard	PW3	19	523	800	13.5 36.5 42	25 42 47
External	Wall	Standard	PW4	25	630	865	42	72











TECHNICAL INFORMATION

The three thicknesses of security glazing which are available offer the following levels of protection.

- 13.5mm laminated security glass for non ballistic resistance against physical attack in accordance with BS 5544 Anti Physical Attack Glazing.
- limiting security glass (firearm resistant) designed to offer protection up to and including the G1 level of BS 5051 Part 1 (1988) Bullet Resistant Security Glazing. Also protects against many forms of shotgun attack.
- 42mm laminated spall limiting security glass (firearm resistant) designed to offer protection to the G2/S86 level of BS 5051 Part 1 (1988).

GLAZING AND BRITISH STANDARD

All manufacture is in general accordance with BS 5357 Code of Practice for Installation of Security Glazing. Please consult Gunnebo personnel about your particular requirements for security glazing.

SURVEY AND INSTALLATION SERVICE

Technical representatives are available throughout the United Kingdom to discuss your requirements and survey premises. Gunnebo can either supply or install the equipment.

OTHER PRODUCTS FROM GUNNEBO

Other products include Security Counters and Screens, Paypoint Modules, Transfer Units, Paypoint Tills and Drawers, Security Doors, Secure Walling, Security Partitioning and Secure Secondary Window Systems.





Bishopsgate Int (Nig) Ltd 52a Campbell Street Lagos Island CBD Lagos State 100221 +234 (700) 247-4677-4283 sales@bishopsgate-ng.com

Tel. Email:

<u>www.bishopsqate-nq.com</u>







Trusted the world over.

Chubbsafes